# LKv 3913

LED

## MediLine

| | |
|---|---|
| **Gross/net capacity** | 386/360 litre |
| **Ext. dimensions in mm** (w/d/h) | 597/615/1840 |
| **Int. dimensions in mm** (w/d/h) | 440/435/1635 |
| Energy consumption in 365 days | 480 kWh |
| Climate rating | SN-ST [1] |
| Refrigerant | R 600a |
| Airborne acoustical noise emissions | 48 dB(A) |
| Connection Rating | 1.5 A |
| Voltage | 220-240 V~ |
| Cooling system | forced-air |
| Defrosting | automatic |
| Temperature range | +2°C to +8°C |
| Gradient * | 5.6°C |
| Max. fluctuation ** | 4.7°C |
| Housing material/colour | steel/white |
| Door/lid material | Insulated glazed door |
| Liner Material | moulded polystyrol white |
| Type of Control | electronic controller |
| Temperature display | external digital |
| Interior light | LED |
| Fault: warning signal | visual and audible |
| Interface | RS 485 |
| volt-free alarm contact | yes |
| Evaporator Cover | yes |
| Adjustable Shelving | 9 |
| Shelf material | grid shelves plastic-coated |
| Shelf loading | 45 kg |
| Handle | Ergonomic door handle |
| Lock | fitted |
| Self-closing door | yes |
| Door hinges | right, reversible |
| Insulation | 40 mm |
| Gross/net weight | 89 / 82 kg |
| EAN-Nr. | 9005382196892 |

Subject to modification. Timestamp: 21.03.2018

1 Climate Ratings: **SN** +10°C to +32°C **N** +16°C to +32°C **ST** +16°C to +38°C **T** +16°C to +43°C

* Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.
** Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.

MEDICAL PRODUCTS
AMA
WESTERN AUSTRALIA
14 Stirling Highway, Nedlands
Western Australia, 6009
(08) 9273 3022
(08) 9273 3017
sales@amawa.com.au

LIEBHERR